

CW AL LSOH Gland Kit

432LSF Series



The only LUL approved industrial cable gland designed for use with LSOH aluminium wire armoured cables.

Features and benefits:

- Indoor & outdoor type for LSOH cable
- Aluminium Indoor & outdoor gland and LSOH accessories
- For Aluminium wire armour LSOH plastic or rubber sheathed cables
- Suitable for most climatic conditions, weatherproof and waterproof
- Three part armour lock with separate armour locking ring, ideal for checking electrical continuity
- No risk of Bi-metallic corrosion when clamping Aluminium armour

Kit comprises

CW-AL (LSOH) Gland
Aluminium earth tag
Aluminium Locknut
LSOH Shroud
(2 per kit up to and including 25mm size)




Technical Information:

- Suitable for use with all Steel Wire Armoured Cables inc: BS 6724 , BS 7835
- Constructed using 6082-T6 Aluminium alloy
- Complies with BS EN 50262 & BS 6121-1: 1989
- Gland rated to IP66 with use of suitable sealing washer or thread sealant at gland interface
- Service temperature range -20°C to + 90°C

Specifications

Gland Kit Reference			Cable Dimensions mm				Gland Dimensions mm				
Design Reference	Size	Qty per Kit	Under Armour Max ϕ (A)	Overall ϕ (B)		Armour Wire ϕ	Entry Thread (D)	Thread Length (E)	Protrusion Length (F)	Hexagon	
				Min	Max					A/F (G)	A/C (H)
432LSF-52	20s	2	11.6	8.0	15.8	0.9	M20x1.5	10	46	25.7	29.2
432LSF-53	20	2	13.9	12.5	20.8	0.9/1.25	M20x1.5	10	46	30.5	34
432LSF-55	25	2	19.9	17.0	27.2	1.25/1.6	M25x1.5	10	51	37.6	42.2
432LSF-56	32	2	26.2	23.5	33.5	1.6/2.0	M32x1.5	10	56	47.3	53.6
432LSF-57	40	2	32.1	29.0	39.9	1.6/2.0	M40x1.5	15	59	56.4	61.5
432LSF-58	50s	1	38.1	38.0	46.2	2.0/2.5	M50x1.5	15	64	65.5	72.1
432LSF-59	50	1	44.0	39.5	52.6	2.0/2.5	M50x1.5	15	64	70.1	77.2
432LSF-61	63	1	55.9	51.3	65.3	2.5	M63x1.5	15	67	80	87.4
432LSF-63	75	1	67.9	62.5	78.0	2.5	M75x1.5	15	76	98.8	109.2



Prysmian Cables & Systems Limited,
Oak Road, Wrexham Industrial Estate, Wrexham, LL13 9PH, UK

Commercial Enquiries,
Sales Office Tel: 0845 767 8345,
International Sales Office Tel: +44 2380 295481

www.biconcomponents.co.uk

