


## UC300 24 Cat.5e

### U/UTP Installation Cable



### Application

Primary (Campus), Secondary (Riser), Tertiary (Horizontal)  
IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T;  
IEEE 802.5 16 MB; ISDN; TPDDI; ATM

### Standards

EIA/TIA 568A;  
ISO/IEC 11801 2<sup>nd</sup> ed.; IEC 61156-5  
EN 50173; EN 50288-3-1

### Flame resistance

PVC: IEC 60332-1  
LSHF IEC 60332-1; IEC 60754-2; IEC 61034

### Construction

Conductor	bare copper wire Ø 0.5 mm (AWG24)
Insulation	Polyethylene, Ø 0.9 mm
Twisting	2 cores to the pair
Cable lay up	4 pairs to the core
Sheath	PVC alt. LSHF (FRNC, LSOH), grey RAL 7035 Duplex sheath: two cables parallel, separable

### Mechanical properties

Minimum bending radius	Installation	8 x D
	Installed	4 x D
Temperature range	during operation	-20°C up to + 60°C
	during installation	0°C up to + 50°C

## UC300 24 Cat.5e

### Electrical properties

at 20°C

DC loop resistance	≤ 190 Ω /km
Resistance unbalance	≤ 2%
Insulation resistance (500 V)	≥ 2000 MΩ *km
Capacitance at 800 Hz	nom. 48 nF/km
Capacitance unbalance (pair to ground)	≤ 1500 pF/km
Mean characteristic impedance 100 MHz	100 ± 5 Ω
Nominal velocity of propagation	approx. 67 %
Propagation delay	Nominal ≤ 535 ns/100m
Delay skew	Nominal ≤ 20 ns/100m
Test voltage (DC, 1 min)	1000 V
Core/Core	
Coupling attenuation	≥ 40 dB

### Electrical data (nominal)

at 20°C

f	Attenuation	NEXT	PS-NEXT	ACR	PS-ACR	ELFEXT	PS-ELFEXT	Return loss
(MHz)	(dB/100m)	(dB)	(dB)	(dB/100m)	(dB/100m)	(dB/100m)	(dB/100m)	(dB)
1	1,9	71	68	69,1	66,1	68	65	20
4	3,7	62	59	58,3	55,3	56	53	23
10	6	56	53	50	47,0	48	45	25
16	7,6	53	50	45,4	42,4	44	41	25
20	8,5	51	48	42,5	39,5	42	39	25
31,2	10,7	49	46	38,3	35,3	38	35	24
62,5	15,7	44	41	28,3	25,3	32	29	22
100	19,8	41	38	21,2	18,2	28	25	20
125	22,3	40	37	17,7	14,7	26	23	19
155,5	24,2	38	35	13,8	10,8	24	21	
175	25,7	37	34	11,3	8,3	23	20	
200	27,5	36	33	8,5	5,5	22	19	
250	29,2	35	32	5,8	2,8	20	17	
300	32,0	34	31	2,0	-1,0	16	13	

## UC300 24 Cat.5e

### Product order data

Product code	Designation	Product name	Outer diameter	Fire load		Weight	Copper content	Max tensile force during installation N
			Mm	MJ/km	kWh/m	kg/km	kg/km	
1000182	J-2YY 4x2x0.5	UC300 24 Cat.5e U/UTP 4P PVC	5.0	365	0.101	35	17.5	100N
1000008	J-2YH 4x2x0.5	UC300 24 Cat.5e U/UTP 4P LSHF		336	0.093	36		
1000249	J-2YY 2x(4x2x0.5)	UC300 24 Cat.5e U/UTP 2x4P PVC	5.0/10.0	730	0.202	70	35	100N
1000353	J-2YH 2x(4x2x0.5)	UC300 24 Cat.5e U/UTP 2x4P LSHF		672	0.186	72		

[PRODUCT CODE TABLE]

© PRYSMIAN GROUP 2008, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.